



**Hydroservice LLC**  
 st. Reytarska, 25 01034, Kyiv, Ukraine  
 +38 (044) 235-72-03 | 270 53 01 | 235 59 02  
 gidroservis2008@ukr.net  
 www.gidroservice.com.ua

### Advantages at a glance:

- The heart of the EcoMaster MK3 are the powerful and reliable ultra-high-pressure pumps of the M-Series, Type 190M and Type 250M.
- Available in three versions with operating pressures of 2,500 bar, 2,800 bar and 3,000 bar.
- Modern, intuitive control.  
(You will find detailed information on our device controllers starting on page 14.)
- Ideal for the removal of coating and concrete refurbishment, as well as for the separation and cutting of various materials.
- Maximum safety for the user: The system is pressureless as long as the high-pressure gun is not activated.
- Low noise operation due to a noise protection hood made from aluminium (<85 dB(A)).
- Approved as a trailer for up to 80 km/h.

### Technical Data EcoMaster MK3

Unit type	190M	250M	190M	250M	190M	250M
Max. pressure in bar		2,500		2,800		3,000
Max. volume flow in l/min	26	32	20	25	18	21
Weight in kg (incl. operating fluids)		2,825		2,825		2,825
Measures in mm (L x W x H)		4,450 × 2,030 × 2,190		4,450 × 2,030 × 2,190		4,450 × 2,030 × 2,190

- 1 With the WOMA high-pressure lances and operating pressures of up to 3,000 bar, even selective concrete removal is possible.
- 2 In combination with the WOMA TD3000 SCS, the EcoMaster MK3 is ideally suited for the uncovering of steel reinforcements and reinforcing bars.
- 3 4 Whether manually using the hand lance or the Magnet Lizard, even multi-layer paints and anti-fouling coatings are no challenge.

